



Durchmesser Diameter		Platzdruck (tatsächlich) Bursting pressure (in fact)	Platzdruck (DIN) Bursting pressure (DIN)	Arbeitsdruck (DIN) Working pressure (DIN)	Biegeradius Bending Radius	Volumenstrom Volume Flow Rate	Theo. Zugfestigkeit Theo. Tensile Strength	Wandstärke Wall Thickness	Gewicht Weight
Inch	mm	bar	bar	bar	mm	L/min (8 bar)	kg	mm	g/m (+/-5%)
3/4	19	75	50	16	190	140	1.800	2,20	195
1	25 / 27	75	50	16	250 / 270	140	2.300	2,00	220
1 1/4	32	65	50	16	320	500	2.700	2,00	270
1 1/2	38	65	50	16	380	500	3.100	2,20	315
1 2/3	42	65	50	16	420	600	3.100	2,00	340
1 3/4	45	65	50	16	450	800	3.300	2,00	350
2	52	60	50	16	520	1.200	3.900	2,30	400
2 1/2	64 / 65 / 66	60	50	16	640 / 650 / 660	1.800	5.200	2,30	575
2 3/4	70	60	50	16	700	1.800	5.800	2,30	620
3	75	60	50	16	750	2.400	7.000	2,50	740
3 1/2	90	50	35	12	900	3.500	7.900	2,80	860
4	102	45	35	12	1.020	4.700	8.200	2,50	1.140
4 1/3	110	45	35	12	1.100	5.200	8.800	2,90	1.140
5	125	45	35	12	1.250	7.000	12.500	3,00	1.260
6	150	38	35	12	1.500	10.000	13.300	3,00	1.700
8	203	35	30	10	2.030	20.000	23.400	3,50	3.000
10	254	on request	on request	on request	on request	on request	on request	on request	on request

Lieferprogramm:

Schläuche ♦ Armaturen ♦ Kugellager ♦ Keilriemen ♦ Antriebselemente ♦ Industriebedarf